

Rim Locks - Traditional

Cylinder Night Latch

1022/L1022

Application:

- For timber doors from 35 to 60mm thick, hinged on the left or right and opening inwards only
- Not recommended for glass panelled doors
- Also suitable for steel and composite doors - special fixings required

Operation:

- The bolt is withdrawn by key outside and knob inside
- The bolt may be held in the locked or in the withdrawn position by operating the snib

Specification:

Reference	1022, L1022 (Lock case only)
Backset	60mm
Case & Keep	Zinc
Latch Bolt	Anodised Brass finish
Knob	Brass
Outside Cylinder	Brass, 5 pin tumbler mechanism
Inside Cylinder	n/a
Keying Groups	May be supplied to pass, differ & master keyed. Supplied with 2 steel nickel plated keys as standard. Masterkeyed products supplied with nickel silver keys
Key Blank Number	KB8-NP

Packaging:

- Available Boxed or Visi Packed
- * boxed only
- ** Visi Packed only



Finish shown: SE-PL

Finishes:

Case only:
CG*, SE*

Case-Cylinder:
CG-PL**, SE-CH;
SE-PL; SE-SC

Standards:



Ordering Code Example:

J 1022 - SE - PL
(Boxed - Product Code - Finish - Cylinder Finish)

Y 1022 - CG - PL
(Visi Packed - Product Code - Finish - Cylinder Finish)
