

3 Lever Mortice

3 Lever Horizontal Mortice Lock

2037

Application:

- For timber doors hinged on the left or right
- Keys are suitable for use on doors up to 54mm thick
- May be supplied master keyed

Operation:

- Deadbolt locked or unlocked by key from either side
- Latch bolt withdrawn by knob or sprung lever handle from either side
- Two way action, suitable for knobs or sprung lever handle (not suitable for unsprung lever handles)
- Pierced to accept bolt through furniture
- May be keyed alike with 2137 and 2237



Specification:

Reference	2037
Case Size	124mm (5") or 149mm (6")
Backset	38mm or 51mm
Case	Steel, silver powder coat
Forend	Stainless steel or brass
Striking Plate	Finished to match forend
Deadbolt	Brass, with hardened steel rollers
Latch Bolt	Brass, easily reversible
Follower	8mm square. Two way action
Rebate Kit	2939 (13mm, 19mm or 25mm)
Keying Groups	May be supplied to pass and master keyed. Supplied with 2 steel nickel plated keys
Key Blank Number	KB483
Keying	500 standard differs (numbers from M1001R to M1500R)

Features:

- Reversible latch bolt
- Available with square forend and striking plate

Finishes:

- SC - Satin Chrome finish
- PL - Polished Brass finish

Standards:

- EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J 2037 - PL - 6.00
(Boxed - Product Code - Finish - Case Size)

