

Rim Locks - Standard Security

Narrow Stile Cylinder Night Latch 1027/L1027

Application:

- For timber doors from 35 to 60mm thick, hinged on the left or right and opening inwards only
- Concealed fixing
- Not recommended for glass panelled doors
- Also suitable for steel and composite doors - special fixings required.

Operation:

- The bolt is withdrawn by key outside and handle inside
- The bolt may be held in the locked or in the withdrawn position by operating the snib

Specification:

Reference	1027, L1027 (Lock case only)
Backset	40mm
Case & Keep	Zinc
Latch Bolt	Anodised Brass finish
Handle	Zinc, finished to match case and keep material
Outside Cylinder	Brass, 5 pin tumbler mechanism
Inside Cylinder	n/a
Keying Groups	May be supplied to pass, differ & master keyed. Supplied with 2 steel nickel plated keys as standard. Masterkeyed products supplied with nickel silver keys
Key Blank Number	KB8-NP

Packaging:

- Available Boxed or Visi Packed
- * boxed only
- ** Visi Packed only



Finish shown: CG-PL

Finishes:

Case only:

 CG*; EB*; SC*; WE*;
CH*; DMG*

Case-Cylinder:

 CG-PL; EB-PL; SC-SC;
WE-PL*; WE-SC*;
CH-CH; DMG-CH;
CG-SC**

Standards:



Ordering Code Example:

 J 1027 - CG - PL
(Boxed - Product Code - Finish - Cylinder Finish)

 Y 1027 - CH - CH
(Boxed - Product Code - Finish - Cylinder Finish)
