

Standard Stile Drawback Lock

1332

Application:

- For timber doors from 35 to 60mm thick, hinged on the left or right and opening inwards only
- Suitable for glass panelled doors
- Also suitable for steel and composite doors - special fixings required

Operation:

- The deadbolt is double thrown, locked or unlocked by key from either side
- The latch bolt is withdrawn by key outside and handle inside
- The latch bolt may be held in by rotating handle

Specification:

Reference	1332
Backset	60mm
Case & Keep	Zinc
Deadbolt	Anodised Brass finish
Latch Bolt	Anodised Brass finish
Handle	Aluminium, finished to match case and keep material
Outside Cylinder	Brass, 5 pin tumbler mechanism
Inside Cylinder	Brass, 2 pin tumbler mechanism
Keying Groups	May be supplied to pass, differ & master keyed. Supplied with 3 steel nickel plated keys as standard. Masterkeyed products supplied with nickel silver keys
Key Blank Number	KB502

Packaging:

- Available Boxed or Visi Packed
- * boxed only
- ** Visi Packed only



Finish shown: WE-PL

Finishes:

Case only:

Only supplied complete with cylinder

Case-Cylinder:

CG-PL; CG-SC*; EB-PL; SC-SC; WE-PL*; WE-SC*; CH-CH; DMG-CH**

Standards:



Ordering Code Example:

J 1332 - CG - PL

(Boxed - Product Code - Finish - Cylinder Finish)

Y 1332 - CH - CH

(Visi Packed - Product Code - Finish - Cylinder Finish)

