

3 Lever Mortice

3 Lever Mortice Sash Lock

2277

2G 3 Lever Mortice

Application:

- For timber doors hinged on the left or right
- Keys are suitable for use on doors up to 54mm thick

Operation:

- Deadbolt locked or unlocked by key from either side
- Latch bolt withdrawn by lever handle from either side
- May be keyed alike with 2077, 2157, 2177 and 2477 (not 51mm case)
- Pierced to accept bolt through furniture

Specification:

Reference	2277
Case Size	51mm(2"), 65mm(2.5"), 77.5mm(3") or 103mm(4")
Backset	32,mm 44.5mm, 57mm or 82.5mm
Case	Steel, silver powder coat
Forend	Stainless steel or brass
Striking Plate	Finished to match forend
Deadbolt	Brass, hardened steel rollers
Latch Bolt	Brass, reversible
Follower	Brass, 8mm square
Rebate Kit	2979 (13mm, 19mm or 25mm)
Keying Groups	May be supplied to pass, differ and keyed alike with 2077, 2157, 2177 and 2477. Supplied with 2 steel nickel plated keys
Key Blank Number	KB436
Keying	2" = 36 standard differs (numbers from M1M to M36M) 2.5", 3" & 4" = 100 standard differs (numbers from M101M to M200M)

NB: Not suitable for master keying



Features:

- Reversible latch bolt
- Available with square forend and striking plate

Finishes:

- SC - Satin Chrome finish
- PL - Polished Brass finish
- CH - Polished Chrome finish (2.5" only)

Standards:



- EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J 2277 - PL - 2.50
 (Boxed - Product Code - Finish - Case Size)
 Y 2277 - PL - 2.50
 (Visi Packed - Product Code - Finish - Case Size)

