

Euro Profile Mortice Night Latch

2349/L2349

Application:

- For timber doors hinged on the left or right
- Also suitable for steel & composite doors - special fixings required

Operation:

- Latch bolt withdrawn by euro profile cylinder from outside and sprung lever handle or separate turn from inside
- Latch bolt is held in the withdrawn position by use of special key supplied (7126-30)
- Reversible latch bolt
- Cylinder options - single cylinder or key and key
- Latch bolt is automatically locked against end pressure by the anti-thrust bolt
- 2349 supplied with 2X20 cylinder

Specification:

Reference	L2349 (lock case & strike plate)
Case Size	77.5mm (3")
Backset	57mm
Case	Steel, silver powder coat
Outer Forend	Stainless steel or brass
Striking Plate	Finished to match forend
Deadbolt	n/a
Latch Bolt	Brass, reversible
Follower	Steel, 8mm square
Rebate Kit	2942 (13mm, 19mm or 25mm)
Cylinder Type	2349 supplied with 2X20 cylinder L2349 euro profile (not supplied)

Features:

- Reversible latch bolt
- Available with square forend and striking plate



Finishes:

- SC - Satin Chrome finish
- PL - Polished Brass finish

Standards:



- EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J - L2349 - PL - 3.00 (case & strike plate only)
J - 2349 - PL - 3.00 (complete with 2X20 cylinder)
(Boxed - Product Code - Finish - Case Size)

