

# Mortice Locks

## BS 5 Lever BS3621:2007 Mortice Sashlock

# 3K74E

**Application:**

- Kitemarked BS3621:2007 sashlock. Approved by insurance companies and the police
- For timber door hinged on the left or the right
- Keys are suitable for use on doors up to 50mm thick

**Operation:**

- Deadbolt is locked or unlocked by key from either side
- Extended 20mm deadbolt for secure positive deadlocking and resistance against attack
- Latch bolt withdrawn by lever handle from either side

**Specification:**

Reference	3K74E
Case Size	67mm and 80mm
Backset	40mm or 53mm
Centres	57mm
Case	Silver powder coat
Forend	Stainless steel or brass
Box Strike Assembly	Painted to match forend
Deadbolt	Brass, with hardened steel rollers
Latch Bolt	Roller bolt (non handed)
Follower	Brass, 8mm square
Keying Groups	Standard differ or to pass (BP codes)
Keys supplied	Standard differ supplied with 3 keys. For locks to pass please specify number of keys required.
Key Blank Number	B-K722 (standard) B-K750 (RKS)
Cut Key Number	B-5LC
NB	Not suitable for master keying
Rebate Kit	B-3K74R (13mm, 19mm and 25mm)

**Features:**

- Force resistant, anti drill, anti-pick and anti-saw security features
- Available with square forend and striking plate
- 20mm bolt throw
- Can be supplied on patented RKS key section to prevent illicit copying of keys
- Can be supplied with either a single or double pole microswitch for alarm systems.


**Finishes:**

- SC - Satin Chrome finish
- PL- Brass finish

**Standards:**

- Tested to BS3621:2007
- EN1634-1 assessed for use on 60 minute timber fire doors



BS3621 : 2007


**Ordering Code Example:**

- B-3K74E-PL-67 (Boxed)
- V-3K74E-SC-67 (Visi packed)
- B-3K74EDP-PL-67 (double pole microswitch)
- B-RKS3K74ESC80 (boxed product with RKS)

